



**'06- YZF-R6
Slip-On**

Thank you for selecting and purchasing a TiForce exhaust system for your Yamaha '06- R6. TiForce is the world's finest titanium exhaust system available today. Please read the following instructions and materials to fully familiarize yourself with new exhaust system before getting started.

Before Installation

- Verify that all parts and accessories have been included (see list below).
 - Coat all exhaust pipe mating joints with anti-seize compound / lubricant.
 - Read and review these instructions, cautions, diagrams and images prior to starting any work.
1. Detach the lower fairing.
 2. Remove the existing silencer and save the band for reuse. Detach the cable of the exhaust valve and make sure the motor remains the previous position during the procedure.
 3. Attach the supplied joint collar to the port of the standard main silencer using the saved standard band saved in step 2.
 4. Insert the supplied silencer to the joint collar.
 5. Lightly attach the silencer to the standard silencer mounting position using supplied bolt and nut. (M8 x 40mm, M8 flange lock nut) .
 6. Reinstall the lower fairing detached in step 1. Make sure the silencer is free and clear; if necessary jiggle the whole to adjust for proper clearance.
 7. Removed the lower fairing reinstalled in step 6. Securely tighten the silencer port using supplied clump band. Using some brake and contact cleaner on a clean rag, carefully wipe down the entire exhaust system to remove any residual oils, anti seize, fingerprints and dirt prior to starting the motor. (Failure to clean the tubing and silencer may result in permanent staining of the system when heated.)
 8. Check that all hardware is tightened, then start the motor and check for exhaust leaks.
 9. Reinstall the fairing and tighten any fasteners per factory specification.

End.



General Cautions For Exhaust System Installations

CAUTION –For your safety, carefully read these instructions and those above, and fully familiarize yourself with the content before beginning installation and use. Keep these instructions in a safe place for future reference. Install the exhaust system as explained in these instructions.

DANGER –when the motor is running, and shortly after it has been turned off, the motorcycle, the exhaust system and end-can will be hot. Severe burns, bodily injury and even death may result.

DANGER –Keep gasoline and other flammable materials away from the exhaust system at all times. Exposure of gasoline and to heat can lead to fire.

CAUTION –Stop the motorcycle should the exhaust system come in contact with people or animals. Never touch the exhaust system when hot. Direct contact with the system can cause burns.

DANGER –Allow the motor to cool before installing or removing the exhaust system. Working with a hot motor can lead to burns.

CAUTION –Stand the motorcycle on a flat and level surface and ensure that the motorcycle is stable before installing the exhaust system. Bodily injury and /or death could result to you or others if the motorcycle falls over. Damage may also result to the motorcycle or nearby property or equipment.

DANGER –Start and run the motorcycle in a well-ventilated area. With prolonged exposure to exhaust gas you run the risk of severe oxygen deficiencies, bodily injury or death may result.

CAUTION –Install the muffler only on the specified model of motorcycle. Improper installation will lead to loss of performance and or damage to the motorcycle.

CAUTION –Do not disassemble, modify or remodel this exhaust system.

TiForce Japan Co., Ltd.
8160-1, Kou-cho,
Suzuka city,Mie
513-0836, Japan

81-593-701881 tel
81-593-701882 fax

<http://tiforce.co.jp>
sales@tiforce.co.jp

Enclosed parts

Silencer	1
Joint collar	1
M8 bolt x 40mm	1
M8 flange lock nut	1
Clump band	1

