



Suzuki '08- GSX-1300R Megaphone Slip-on

Thank you for selecting and purchasing a TiForce exhaust system for your Suzuki GSX1300R. TiForce is the world's finest titanium exhaust system available today. Please read the following instructions and materials to fully familiarize yourself with your new exhaust system before getting started. Instructions are also available in Adobe Acrobat PDF format on the TiForce website (www.tiforce.com).

Before Installation

- Verify that all parts and accessories have been included (see list below).
 - Coat all exhaust pipe matching joints with anti-seize compound / lubricant.
 - Read and review these instructions, cautions, diagrams and images prior to starting any work.
 - TiForce recommends the use of light-duty thread locking agent (ie Blue Loctite) on all exhaust mounting fasteners – especially the fasteners on passenger footrest brackets and all silencers mounting hardware.
1. Remove the L and R stock silencers.
 - *save stock nuts and bolts for reuse
 - *Take off the clamp band from the stock silencer and save it for reuse
 2. Attach the TiForce L and R megaphone.
 - *Attach the clamp band saved from step 1 to inlet of the TiForce megaphone and insert the megaphone to the stock exhaust pipe section.
 - *Attach the TiForce megaphone to the stock passenger's foot peg stay using by the stock nut and bolt saved from step 1.
 - *Fasten the clamp band.
 3. Make sure the exhaust system is free and clear of the bike and fairing. If necessary, adjust for proper clearance.
 4. Using some brake and contact cleaner on a clean rag, carefully wipe down the entire exhaust system to remove any residual oils, anti seize, fingerprints and dirt prior to starting the motor. **FAILURE TO CLEAN THE TUBING AND CAN MAY RESULT IN PERMANENT STAINING OF THE SYSTEM WHEN HEATED.**
 5. Check nuts and bolts are securely fastened.
 6. Start the engine and check for exhaust leaks.

END

Enclosure:

TiForce Light Megaphone	1 pc
TiForce Right Megaphone	1 pc

TiForce Japan Co., Ltd	81-593-701881 tel	http://www.tiforce.com
8160-1,Kou-cho	81-593-701882 fax	sales@tiforce.com
Suzuka city, Mie		
513-0836, Japan		

For North America Users: Replacement parts availability at US office, #205-583-8601 voice, tech@tiforce.com

General Cautions for Exhaust System Installations

CAUTION –For your safety, carefully read these instructions and those above, and fully familiarize yourself with the content before beginning installation and use. Keep these instructions in a safe place for future reference. Install the exhaust system as explained in these instructions.

DANGER –when the motor is running, and shortly after it has been turned off, the motorcycle, the exhaust system and end-can will be hot. Severe burns, bodily injury and even death may result.

DANGER –Keep gasoline and other flammable materials away from the exhaust system at all times. Exposure of gasoline and to heat can lead to fire.

CAUTION –Stop the motorcycle should the exhaust system come in contact with people or animals. Never touch the exhaust system when hot. Direct contact with the system can cause burns.

DANGER –Allow the motor to cool before installing or removing the exhaust system. Working with a hot motor can lead to burns.

CAUTION –Stand the motorcycle on a flat and level surface and ensure that the motorcycle is stable before installing the exhaust system. Bodily injury and /or death could result to you or others if the motorcycle falls over. Damage may also result to the motorcycle or nearby property or equipment.

DANGER –Start and run the motorcycle in a well-ventilated area. With prolonged exposure to exhaust gas you run the risk of severe oxygen deficiencies, bodily injury or death may result.

CAUTION –Install the muffler only on the specified model of motorcycle. Improper installation will lead to loss of performance and or damage to the motorcycle.

CAUTION –Do not disassemble, modify or remodel this exhaust system.

